

"Express Mail" Mailing Label No.: EL 303829625 US

Date of Deposit: March 15, 2004

Attorney Docket No. 13912US05

SYSTEM AND METHOD TO REDUCE NOISE IN A SUBSTRATE

CROSS-REFERENCE TO RELATED APPLICATIONS/INCORPORATION BY REFERENCE

PC
5/18/05

[01] This application is a continuation of United States Application Serial No. 10/294,880 filed on November 14, 2002, ^{Patent No. 6,870,228,} which makes reference to, claims priority to and claims the benefit of United States Provisional Patent Application Serial No. 60/402,095 filed on August 7, 2002, *and claims the benefit of United States Provisional Patent Application Serial No. 60/402,090 filed on August 9, 2002.*

[02] All of the above stated applications are incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

[03] Certain embodiments of the invention relate to integrated circuit (IC) designs. More specifically, certain embodiments of the invention relate to a system for reducing noise in a substrate of an integrated circuit.

BACKGROUND OF THE INVENTION

[04] As more and more functional blocks are added, for example, to a chip, an integrated circuit (IC) or an integrated system or device, the risk for the generation and propagation of noise between the different functional blocks or within a functional block may become quite substantial.

[05] An exemplary conventional complementary metal oxide semiconductor (CMOS) transistor arrangement is illustrated in FIG. 1. As shown in FIG. 1, the conventional CMOS transistor arrangement 10 includes an n-channel MOS (NMOS) transistor 30 and a p-channel MOS (PMOS) transistor 40. The conventional CMOS arrangement 10 also includes a p-substrate 20 (e.g., a p⁻-substrate). The NMOS transistor 30 is disposed in the p-substrate 20. The NMOS transistor 30 includes a p⁺-body (B), an n⁺-source (S)